

Blastpro Mfg.

Lavina

Prepmaster

National

Ermator

Prosoco

PowerBoss

Factory Cat

Tennant

Sweepex

Diamonds

Parts

Used Equipment

Rentals

10 Sales Locations

5 Service Locations

325 West Front St.
Erie, PA 16507
814-455-8838
814-454-0160 - FAX

5324 Wilkinson Blvd.
Charlotte, NC 28208
704-395-1258
704-394-0909 - FAX

Bloomfield Bus. Park
415 Bloomfield Drive
W. Berlin, NJ 08091
856-767-1863
856-767-1746 - FAX

Blastpro Manufacturing
6021 Melrose Lane
Oklahoma City, OK 73127
405-491-6464

Blastpro Manufacturing
210 E. Emerson Ave.
Orange, CA 92865
714-282-6900

BLASTPRO BP-15-SUPER



SPECIFICATIONS

The BP-15 Super is designed for medium to large jobs including: industrial plants, warehouse floors, parking garages, bridge decks, ship decks, storage tanks and other horizontal applications. The BP-15 Super is an electric self-propelled walk-behind machine. It is equipped with a 15" blast pattern, high quality electrical components, and an advanced air wash separation system. The BP-15 Super operates on 208/230/460 volt three phase power. The BP-15 travels up to 100 ft. per minute and has a production capacity of up to 1,950 sq. ft. per hour.

Production Capacity	1,950 sq. ft. /hr.
Blast Pattern	15"
Travel Speed	0-100 ft. /min.
Blast Motor	20 h.p.
Voltage	208/230/460 3phase
Amperage	50 amps @ 230v & 24@480v
Minimum Generator	60 kw
Dimensions	72"x23"x41"
Weight	847 lbs.
Power Cord Length	55 ft.
Seals	Mag / wrap around seal
Distance to edge	2.5"
Dust Collector	BP-9-54

ADVANTAGES

- All wear parts and equipment are manufactured in the USA, typically no lead time when ordering parts.
- The electrical box and components are engineered and constructed by a UL508A Panel Facility.
- The electrical enclosures are built to NEMA 4 specifications.
- Positive sealing shot valve prevents leaking even when using small shot.
- Interlocking liners protect the blast housing and reduce wear.
- Sliding cleanout drawer allows quick and easy removal of debris from shot hopper.
- Improved separation system keeps shot cleaner, increases the life of wear parts.
- The high speed bearing unit contains replaceable bearings which reduces operating costs and down time.
- W 4/4 electrical cord is the toughest and most wear resistant cord available.

**Production rates are estimates only. Production rates are dependent on job site and application variables.*

Sales Representatives



Kenny Boone
Memphis, TN
901-619-2244



Pat Coughenaur
Cleveland, OH
317-603-5462



Roger Cowan
Rochester, NY
901-619-2244



Rick Gorchinsky
Customer Support
814-455-8838



Willie Heath
Customer Support
704-395-1258



Kevin Hill
Charlotte, NC
704-914-5404



Scott Johnson
Lavina Product
Specialist
412-215-9844



Bill Marsh
Steel Market
Specialist
856-767-1863



Jake Paulus
Customer Support
814-455-8838



Brian Small
Phila, NYC, DC
856-767-1863



Jim Sullivan
Phila, NYC, DC
609-923-5355



Bobby Watson
Western Region
405-996-0714